



PRO-TURN 600



MEET YOUR NEW EMPLOYEE OF THE MONTH FOR THE FORESEEABLE FUTURE.

When you add a Pro-Turn 600 to your crew, it's kind of like adding another employee. It cuts faster and more efficiently, handling more work in less time. Its Operator Pod System was designed to keep you mowing comfortably sunrise to sunset, cutting back on driver fatigue.

Best of all, it will impress both your clients and any potential crew members because they'll see you only use the best.



52"

MODEL - 992500

27 HP / 999 Kawasaki® FX850 Engine

60"

MODEL - 992501

35 HP / 999 Kawasaki® FX1000 Engine

MODEL - 992503

38.5 HP / 999 Kawasaki® FX1000V-EFI Engine

72"

MODEL - 992502

35 HP / 999 Kawasaki® FX1000 Engine

MODEL - 992504

38.5 HP / 999 Kawasaki® FX1000V-EFI Engine

DIAL-A-HEIGHT This lets the operator easily adjust the deck height by quarter-inch increments.

LARGE-DIAMETER TIRES Both the front and rear tires provide a smoother ride and more traction in varying conditions.

X-FACTOR® 3 DECK The deck has been completely redesigned for better grass dispersion. Its new look is constructed from 7-gauge steel to deliver years of solid performance.

PRO-TURN® 600



See your professional Gravely® dealer for complete warranty details.

	652	660	660	672	672
MODEL NUMBER	992500	992501	992503	992502	992504
ENGINE	KAWASAKI ¹ FX850V	KAWASAKI ¹ FX1000	KAWASAKI ¹ FX1000V-EFI	KAWASAKI ¹ FX1000	KAWASAKI ¹ FX1000V-EFI
HORSEPOWER	27 HP	35 HP	38.5 HP	35 HP	38.5 HP
DISPLACEMENT	852 CC	999 CC	999 CC	999 CC	999 CC
DRIVE SYSTEM	PARKER HTG TRANSMISSION				
FUEL CAPACITY	12.7 GAL				
GROUND SPEED (APPROX. Mph) (Forward/ Reverse)	15 MPH / 6 MPH				
DECK					
DECK MATERIAL	7 GA. STEEL WITH .25 IN. SPINDLE REINFORCEMENT				
DECK CONSTRUCTION	FABRICATED X-FACTOR III				
NUMBER OF SPINDLES	3				
BLADE TIP SPEED (FPM)	18,000				
SPINDLE HOUSING MATERIAL	FORGED ALUMINUM				
SPINDLE BEARINGS	BALL BEARING				
DECK ENGAGEMENT	OGURA ² GT3.5 ELECTRIC CLUTCH				
CUTTING WIDTH	52 IN	60 IN	60 IN	72 IN	72 IN
CUTTING HEIGHTS	1.0 IN - 5.5 IN				
CUTTING POSITIONS	19				
WHEELS					
FRONT AXLE	FIXED, GREASEABLE CASTER FORK TUBES				
FRONT	SMOOTH 15 X 6-6 SEMI PNEUMATIC				
REAR	26 X 12-16 LOW PROFILE RADIAL TURF				
FEATURES					
SEAT	HIGH BACK BOLSTERED WITH SUSPENSION POD SYSTEM				
FOLDABLE ROPS	STANDARD				
MACHINE					
WEIGHT	1535 LBS	1586 LBS	1601 LBS	1646 LBS	1661 LBS
LENGTH	83 IN				
WIDTH (w/o CHUTE)	55 IN	63 IN	63 IN	75 IN	75 IN
WIDTH (w/ CHUTE)	63 IN	75 IN	75 IN	87 IN	87 IN
HEIGHT (w/ ROPS EXT/DOWN)	71.5 IN / 47.8 IN				
WARRANTY					
UNIT	5 YEAR / 1500 HOUR COMMERCIAL / NO HOUR LIMIT FIRST 2 YEARS - SEE YOUR PROFESSIONAL GRAVELY® DEALER FOR COMPLETE WARRANTY DETAILS				
DECK SHELL & FRAME	LIMITED LIFETIME				
ATTACHMENTS & ACCESSORIES					

MULCHING KIT, TRAILER HITCH KIT, LED HEADLIGHT KIT, STRIPING KIT, POWERED BAGGER KIT, OCDB KIT, SUNSHADE KIT, REAR TWEEL KIT, SEMI-PNEUMATIC FRONT TIRE KIT, RADIAL DRIVE CONVERSION KIT, WHEEL COVER KIT, AIR RIDE SEAT KIT, LASEREDGE BLADES, TUNE UP KIT, OCDB KIT, SUNSHADE KIT, REAR TWEEL KIT, SEMI-PNEUMATIC FRONT TIRE KIT, RADIAL DRIVE CONVERSION KIT, WHEEL COVER KIT, AIR RIDE SEAT KIT, LASEREDGE BLADES, TUNE UP KIT

