



# AXIS

VERSATILITY  
AND EFFICIENCY  
MEET AT THIS  
AXIS POINT.



Introducing the Gravely Axis, a multi-tool machine that puts a heavy emphasis on “multi.” It performs a ton of jobs but its main one is maximizing a crew’s time in the field. With its list of attachments and capabilities, it’s not a machine that will sit idle. On the 200 Series models you can also customize its hydraulics to put its brawn where and when you need it. Welcome the Axis, where you’re the pivot point to all its power.



## 200DW

MODEL - 950012

25 HP / Kubota® D1105

## 200DT

MODEL - 950010

25 HP / Kubota® D1105

## 200DTN

MODEL - 950011

25 HP / Kubota® D1105

**VERSATILITY** Due to compact design

**POWERFUL DIESEL ENGINES** Models feature Kubota D1105 25 HP Diesel engines.

**TIRES OR TRACKS** Models include big 18 x 8.5 x 8 Turf Saver Tires, 7” or 9” imbedded steel rubber tracks. All models can switch from wheel to track or track to wheel with factory kit.

**DRIVER PLATFORM** Stand-on position for easy dismount and dash panel access.

**SELF-LEVELING BOOM** The automatic self-leveling booms that will keep the bucket, pallet forks or attachment level so the operator does not need to keep making adjustments when raising or lowering the boom to allow for more efficient operation.

**VARIABLE FLOW SYSTEM** Variable Flow control allows precise adjustment of the hydraulic flow to allow inching when trenching.

	200DW	200TN	200T
<b>MODEL NUMBER</b>	950012	950011	950010
<b>DESCRIPTION</b>	DIESEL WHEELED	DIESEL NARROW TRACK	DIESEL WIDE TRACKED
<b>DRIVE TIRES</b>	18 X 8.5 X 8 BAR TREAD TIRES	N/A	N/A
<b>TRACKS</b>	N/A	7"	9"
<b>DIMENSIONS AND WEIGHT</b>			
<b>LENGTH W/STD BUCKET</b>		79.8 IN.	
<b>LENGTH W/O STD BUCKET</b>		63.3 IN.	
<b>WIDTH W/STD BUCKET</b>	42 IN.	36 IN.	42 IN.
<b>WIDTH W/O BUCKET</b>	41 IN.	35.5 IN.	41.5 IN.
<b>WEIGHT W/O STD BUCKET</b>	2,100 LBS.	2,500 LBS.	2,600 LBS.
<b>HEIGHT</b>			
<b>OVERALL OPERATING HEIGHT</b>	84 IN.		85 IN.
<b>HEIGHT AT 45 DEGREE DUMP ANGLE</b>	47.8 IN.		48.8 IN.
<b>GROUND CLEARANCE</b>		6.0 IN.	
<b>ENGINE</b>			
<b>MAKE</b>		KUBOTA	
<b>MODEL</b>		D1105	
<b>FUEL TYPE</b>		DIESEL	
<b>FUEL TANK CAPACITY</b>		10 GALLON	
<b>GROSS HP</b>		25 HP	
<b>COOLING SYSTEM</b>		LIQUID	
<b>MAX INCLINE ANGLE</b>		72 DEGREES	
<b>PERFORMANCE</b>			
<b>MAX LIFT CAPACITY</b>	631 LBS. @ 50% OF TIPPING LOAD	497 LBS. @ 35% OF TIPPING LOAD	489 LBS. @ 35% OF TIPPING LOAD
<b>TIPPING CAPACITY</b>	1,262 LBS.	1,420 LBS.	1,397 LBS.
<b>TOP SPEED</b>	3.2 MPH		3.5 MPH
<b>OPERATIONAL</b>			
<b>STEERING</b>		SINGLE PALM HAND STEERING	
<b>LIFT</b>		SINGLE JOYSTICK	
<b>CURL</b>		SINGLE JOYSTICK	
<b>HYDRAULIC SYSTEM</b>			
<b>AUX SYSTEM FLOW</b>		14 GPM	
<b>LOW FLOW</b>		5.5 GPM	
<b>SYSTEM PRESSURE</b>		3,000 PSI	
<b>GROUND PRESSURE</b>	4.2 PSI	4.2 PSI	4.2 PSI
<b>TANK CAPACITY</b>		11 GALLON	
<b>ATTACHMENTS OFFERED</b>			
<b>36' BUCKET</b>		X	
<b>42" BUCKET</b>	X	X	X
<b>PALLET FORKS</b>	X	X	X
<b>WARRANTY</b>			
<b>UNIT</b>	1 YEAR/1000 HOUR COMMERCIAL, 3 YEAR ENGINE		

