

IT HAS QUIETLY SILENCED ANY DOUBT.

Welcome to superior battery technology from FusionCore. The EV's four swappable batteries deliver the all-day, reliable high-performance power you need in a commercial mower. No pullies, belts, engine oil changes, or driving vibrations. They've been replaced with the quiet hum of success.



48"

GRAVELY

MODEL - 997005 4 Lithium-Ion Swappable Batteries Side Discharge

MODEL - 997008 4 Lithium-Ion Swappable Batteries Rear Discharge 52" MODEL - 997006

4 Lithium-Ion Swappable Batteries Side Discharge

MODEL - 997009 4 Lithium-Ion Swappable Batteries Rear Discharge **60 MODEL - 997007** 4 Lithium-Ion Swappable Batteries Side Discharge

MODEL - 997010 4 Lithium-Ion Swappable Batteries Rear Discharge

X3 CONSTANT DRIVE SPINDLES Our proprietary spindles have a blade slip feature that prevents damage in the event of an impact. They also have a bottom bearing for easy serviceability for routine maintenance which avoids the need to replace the entire spindle.

NEXT-GEN WHEEL DRIVES Transaxles are driven with a brushless electric-drive motor coupled with a dual-reduction planetary gearbox.

LCD DISPLAY High-tech display screen keeps the operator in the know with information on battery charge, blade engagement, and alerts if an issue needs to be addressed.

X-FACTOR® 3 DECK The deck has been completely redesigned for better grass dispersion. Its new look is constructed from 7-gauge steel to deliver years of solid performance.

PRO-TURN[®] EV



See your professional Gravely® dealer for complete warranty details.

	EV 48 SD	EV 48 RD	EV 52 SD	EV 52 RD	EV 60 SD	EV 60 R
MODEL NUMBER	997005	997008	997006	997009	997007	997010
BATTERIES	4 - 16 KWH FUSION CORE LITHIUM ION					
WHEEL DRIVE MOTORS	5 KW PER MOTOR					
SPINDLE MOTORS	3.5 KW PER MOTOR					
DRIVE SYSTEM	PROPRIETARY ELECTRIC TRANSAXLES					
GROUND SPEED Approx. Mph) (Forward/Reverse)	8 MPH / 4MPH (LOW SPEED) – 11 MPH / 5.5 MPH (HIGH SPEED)					
DECK						
DECK MATERIAL	7 GA.					
DECK CONSTRUCTION	X-FACTOR 3° DECK					
IUMBER OF SPINDLES	3					
BLADE TIP SPEED (FPM)	18,000					
PINDLE HOUSING MATERIAL	CAST ALUMINUM					
PINDLE BEARINGS	SERVICEABLE BOTTOM BEARING					
ECK ENGAGEMENT	ELECTRIC DC BRUSHLESS MOTORS					
UTTING WIDTH	48 IN.	48 IN	52IN	52 IN	60 IN	60 IN
UTTING HEIGHTS	1.5 IN 5.0 IN.					
UTTING POSITIONS	15					
HEELS						
RONT AXLE	FIXED, GREASEABLE CASTER FORK TUBES					
RONT	SM00TH 13 X 6.5-6					
EAR	RADIAL TURF 22 X 10-12 RADIAL TURF 22 X 10.5-12			RADIAL TURF 22 X 12-12		
EATURES						
EAT	HIGH BACK COMFORT WITH SUSPENSION					
OLDABLE ROPS	STANDARD					
ACHINE						
VEIGHT	1261 LBS.	1286 LBS.	1284 LBS.	1301 LBS.	1312 LBS.	1326 LBS.
ENGTH	83 IN.					
VIDTH (w/o CHUTE)	50 IN.	50 IN.	56 IN.	54 IN.	63 IN.	64 IN.
VIDTH (w/ CHUTE)	62 IN.	50 IN.	67 IN.	54 IN.	75 IN.	62 IN.
EIGHT (w/ ROPS EXT/DOWN))	72 IN / 49 IN.					
VARRANTY						
INIT	5 YEAR / 1500 HOUR CO	MMERCIAL / NO HOUR LIM	T FIRST 2 YEARS - SEE YO	UR PROFESSIONAL GRAVEL	Y® DEALER FOR COMPLET	E WARRANTY DET

ATTACHMENTS & ACCESSORIES

FUSIONCORE OFF BOARD PORTABLE CHARGER, REPLACEMENT BATTERIES, MULCHING KIT, LED HEADLIGHT KIT, BEACON LIGHT KIT, FAST CHARGE KIT WITH Y HARNESS, HIGH-LIFT BLADE KIT, OCDB KIT, FRONT CASTOR SUSPENSION FORKS, REAR TWEEL KIT, FRONT WEIGHT KIT



SCAN TO VIEW

PRODUCT ONLINE

© Copyright 2022 AriensCo. All rights reserved. Registered trademark and [™] trademark of Ariens Company. Briggs & Stratton*, Kohler*, Kawasaki*, Subaru*, Yamaha* and Hydro-Gear* are registered trademarks of their respective companies. The engine horsepower information is provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower will be less. Visit gravely.com for a complete listing of engine manufacturrating information. Product features and specifications subject to change without notice. Photos are a representation of the product; actual product may vary.

